



NTA BEARING PRECISION AXLE CORP.



skf SA 15 C Spherical plain bearings and rod ends with a male thread

Bearing No. SA 15 C

SA 15 C Bearing 2D drawings and 3D CAD models

Category	Spherical Plain Bearings - Rod Ends
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.13
EAN	7316577104892
Product Group	B04286
Stud Profile	Male
Mounting Thread	M14 X 2
Thread Direction	Right Hand
Rolling Element	Spherical Plain
Material - Outer Member	Steel
Material - Ball	Steel
Material - Liner	Teflon Sintered Bronze
Relubricatable	No
Enclosure	Open
Other Features	3 Piece Zinc Plated Outer Self Lubricating Maintenance Free
Long Description	15MM Bore; 10.5MM House Width; Male Stud Profile; M14 X 2; Right Hand Thread Direction; Spherical Plain Bearing; Steel Outer Member; Steel Ball; Teflo
Inch - Metric	Metric



NTA BEARING PRECISION AXLE CORP.

Category	Plain Bearing Spherical Rod Ends
UNSPSC	31171508
Harmonized Tariff Code	8483.30.80.55
Noun	Bearing
Keyword 3	Rod End
Keyword String	Plain Spherical Rod End
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	SA 15 C
Weight / LBS	0.287
Ball Width	0.472 Inch 12 Millimeter
Housing Width	0.413 Inch 10.5 Millimeter
d	0.591 Inch 15 Millimeter
bore diameter:	15 mm
ball material:	Steel
misalignment angle:	8 °
race material:	Bronze
shank thread length:	34 mm
radial static load capacity:	34.5 kN
rod end type:	Male Threaded
operating temperature range:	-50 to +150 ° F
shank thread size:	M14
head diameter:	41 mm
thread direction:	Right Hand
head width:	10.5 mm
grade:	Commercial/Industrial
ball width:	12 mm
lubrication type:	Maintenance Free/Self-Lubricating
length to ball center:	63 mm
housing material:	Zinc-Plated Steel
standards met:	ISO 12240-4:1998, ISO



NTA BEARING PRECISION AXLE CORP.

	965-1:1998
d	15 mm
d ₂ max.	41 mm
B	12 mm
G	M 14
C ₁ max.	10.5 mm
h	63 mm
	8 °
d _k	22 mm
l ₁ min.	34 mm
l ₂ max.	85 mm
l ₇ min.	19 mm
r ₁ min.	0.3 mm
Basic dynamic load rating C	18 kN
Basic static load rating C ₀	34.5 kN
Specific dynamic load factor K	100 N/mm ²
Material constant K _M	1400
Mass rod end	0.13 kg